

MP-1001EIE-02 Metered PDU

1U Single Phase Metered

MP-1001 is our Basic 1U PDU delivering Single-Phase power to 8x outlets. These cost-effective PDUs reliably deliver unfiltered power to your equipment while meeting budget demands. Ideal for Datacenters, IT Racks, Engineering Labs, and more!

Metered PDU Features

- Slim/Space Efficient Form Factor
- Inlet Current Measurements
- Local Amperage Meter
- Industrial Steel Enclosure
- UL/CSA 62368-1 : 2019 Third Edition Compliant

What's Included

- Detachable NEMA 5-15P to C19 Cord (6ft)
- 1U Mounting Brackets with M4 Screws
- Quick Start Guide Reference Pamphlet

Key Stats

Form Factor: 1U

Max Input Current: 20A (16A)

Power Capacity: 1.9kVA,3.3kVA,3.8 kVA

Inlet Voltage(s): 120V,208V,240V

Outlets: 8

Applications

- Mission critical remote installations.
- IT server racks.
- Datacenters
- Production automation.
- Test automation.
- Engineering labs.
- R&D facilities.

Features



Input Power Measurements
Current Measurements at Input



Local Current Display
7-Segment LED Display to display current consumption.

Specifications

| Input | |
|-----------------------------|----------------|
| Plug Type | IEC-320 C20 |
| Input Voltage | 120V,208V,240V |
| Max Input Current (Derated) | 20A (16A) |
| Phase | 1 |

| Output | |
|-------------------------|-----------------------|
| Outlet Receptacles | C13(8) |
| Total Number of Outlets | 8 |
| Power Capacity | 1.9kVA,3.3kVA,3.8 kVA |
| Overload Protection | None |

| Physical | |
|-----------------------------|---------------------------|
| Form Factor | 1U |
| Dimensions | 17.00" x 1.75" x 2.50" |
| Maximum Operating Elevation | 0-10,000 ft / 0 - 3,000 m |
| Operating Temperature Range | 0C to +65C |
| Relative Humidity | 5-95% (non-condensing) |