

# MP-2001EIE-05 Metered PDU

## 2U Single Phase Metered

MP-2001 is our Basic 2U PDU delivering Single-Phase power to 16x outlets. These cost-effective PDUs reliably deliver unfiltered power to your equipment while meeting budget demands. Ideal for Datacenters, IT Racks, Engineering Labs, and more!

### Metered PDU Features

- Slim/Space Efficient Form Factor
- Inlet Current Measurements
- Local Amperage Meter
- Industrial Steel Enclosure
- UL/CSA 62368-1 : 2019 Third Edition Compliant

### What's Included

- Detachable NEMA 5-15P to C19 Cord (6ft)
- 2U Mounting Brackets with M4 Screws
- Quick Start Guide Reference Pamphlet

### Key Stats

Form Factor: 2U

Max Input Current: 20A (16A)

Power Capacity: 1.9kVA,3.3kVA,3.8 kVA

Inlet Voltage(s): 120V,208V,240V

# Outlets: 16

### Applications

- Mission critical remote installations.
- IT server racks.
- Datacenters
- Production automation.
- Test automation.
- Engineering labs.
- R&D facilities.

## Features



**Input Power Measurements**  
Current Measurements at Input



**Local Current Display**  
7-Segment LED Display to display current consumption.

## Specifications

### Input

Plug Type	IEC-320 C20
Input Voltage	120V,208V,240V
Max Input Current (Derated)	20A (16A)
Phase	1

### Output

Outlet Receptacles	C13(16)
Total Number of Outlets	16
Power Capacity	1.9kVA,3.3kVA,3.8 kVA
Overload Protection	None

### Physical

Form Factor	2U
Dimensions	17.00" x 3.50" x 4.31"
Maximum Operating Elevation	0-10,000 ft / 0 - 3,000 m
Operating Temperature Range	0C to +65C
Relative Humidity	5-95% (non-condensing)