

# MP-3001ENA-0D Metered PDU

## 3 Phase Delta Metered

MP-3001 is our Basic 0U PDU delivering power to 36x outlets in a 3-Phase Delta configuration. The outlets are divided into 9x alternating phase groups to help you easily balance your loads. These cost-effective PDUs reliably deliver unfiltered power to your equipment while meeting budget demands. Ideal for Datacenters, IT Racks, Engineering Labs, and more!

### Metered PDU Features

- Slim/Space Efficient Form Factor
- Inlet Current Measurements
- Local Amperage Meter
- Industrial Steel Enclosure
- UL/CSA 62368-1 : 2019 Third Edition Listed

### What's Included

- Attached NEMA L15-20P Plug
- 0U Mounting Bracket with M4 Screws
- 0U Toolless Button Kit
- Quick Start Guide Reference Pamphlet

### Key Stats

Form Factor: 0U

Max Input Current: 20A (16A)

Power Capacity: 5.8 kVA

Inlet Voltage(s): 208V

# Outlets: 36

### Applications

- Mission critical remote installations.
- IT server racks.
- Datacenters
- Production automation.
- Test automation.
- Engineering labs.
- R&D facilities.



## Features



**Input Power Measurements**  
Current Measurements at Input



**Alternating Phase Groups**  
3-Phase PDUs with this feature have alternating phases on every group of 4 outlets.



**Local Current Display**  
7-Segment LED Display to display current consumption.

## Specifications

### Input

|                             |              |
|-----------------------------|--------------|
| Plug Type                   | NEMA L15-20P |
| Input Voltage               | 208V         |
| Max Input Current (Derated) | 20A (16A)    |
| Phase                       | 3            |

### Output

|                         |                              |
|-------------------------|------------------------------|
| Outlet Receptacles      | C13(30) + C19(6) Alternating |
| Total Number of Outlets | 36                           |
| Power Capacity          | 5.8 kVA                      |
| Overload Protection     | None                         |

### Physical

|                             |                           |
|-----------------------------|---------------------------|
| Form Factor                 | 0U                        |
| Dimensions                  | 70.00" x 2.20" x 2.20"    |
| Maximum Operating Elevation | 0-10,000 ft / 0 - 3,000 m |
| Operating Temperature Range | 0C to +65C                |
| Relative Humidity           | 5-95% (non-condensing)    |