

# MP-3101EIH-0A-001 Metered PDU

## 3 Phase Wye Metered

MP-3101 is our Basic 0U PDU delivering power to 36x outlets in a 3-Phase WYE configuration. The outlets are divided into 9x alternating phase groups to help you easily balance your loads. These cost-effective PDUs reliably deliver unfiltered power to your equipment while meeting budget demands. Ideal for Datacenters, IT Racks, Engineering Labs, and more!

### Metered PDU Features

- Slim/Space Efficient Form Factor
- Inlet Current Measurements
- Local Amperage Meter
- Industrial Steel Enclosure
- UL/CSA 62368-1 : 2019 Third Edition Compliant

### What's Included

- Attached Plug
- 0U Mounting Bracket with M4 Screws
- 0U Toolless Button Kit
- Quick Start Guide Reference Pamphlet

### Key Stats

Form Factor: 0U

Max Input Current: 60A (48A)

Power Capacity: 17.3 kVA, 16.6 kVA

Inlet Voltage(s): 400V, 415V

# Outlets: 36

### Applications

- Mission critical remote installations.
- IT server racks.
- Datacenters
- Production automation.
- Test automation.
- Engineering labs.
- R&D facilities.

## Features



**Input Power Measurements**  
Current Measurements at Input



**Alternating Phase Groups**  
3-Phase PDUs with this feature have alternating phases on every group of 4 outlets.



**Local Current Display**  
7-Segment LED Display to display current consumption.

## Specifications

Input	
Plug Type	
Input Voltage	400V,415V
Max Input Current (Derated)	60A (48A)
Phase	

Output	
Outlet Receptacles	C13(36)
Total Number of Outlets	36
Power Capacity	17.3 kVA,16.6 kVA
Overload Protection	6 x 1 Pole CBs

Physical	
Form Factor	0U
Dimensions	70.00" x 2.20" x 2.20"
Maximum Operating Elevation	0-10,000 ft / 0 - 3,000 m
Operating Temperature Range	0C to +65C
Relative Humidity	5-95% (non-condensing)