

MP-4001EIE-09 Metered PDU

0U Single Phase Metered

MP-4001 is our Basic 0U PDU delivering Single-Phase power to 24x to 36x outlets. These cost-effective PDUs reliably deliver unfiltered power to your equipment while meeting budget demands. Ideal for Datacenters, IT Racks, Engineering Labs, and more!

Metered PDU Features

- Slim/Space Efficient Form Factor
- Inlet Current Measurements
- Local Amperage Meter
- Industrial Steel Enclosure
- UL/CSA 62368-1 : 2019 Third Edition Listed

What's Included

- Detachable NEMA 5-15P to C19 Cord (6ft)
- 0U Mounting Bracket with M4 Screws
- 0U Toolless Button Kit
- Quick Start Guide Reference Pamphlet

Key Stats

Form Factor: 0U

Max Input Current: 20A (16A)

Power Capacity: 1.9kVA,3.3kVA,3.8 kVA

Inlet Voltage(s): 120V,208V,240V

Outlets: 24

Applications

- Mission critical remote installations.
- IT server racks.
- Datacenters
- Production automation.
- Test automation.
- Engineering labs.
- R&D facilities.



Features



Input Power Measurements
Current Measurements at Input



Local Current Display
7-Segment LED Display to display current consumption.

Specifications

Input	
Plug Type	IEC-320 C20
Input Voltage	120V,208V,240V
Max Input Current (Derated)	20A (16A)
Phase	1

Output	
Outlet Receptacles	C13(20) + C19(4)
Total Number of Outlets	24
Power Capacity	1.9kVA,3.3kVA,3.8 kVA
Overload Protection	None

Physical	
Form Factor	0U
Dimensions	58.13" x 2.20" x 2.20"
Maximum Operating Elevation	0-10,000 ft / 0 - 3,000 m
Operating Temperature Range	0C to +65C
Relative Humidity	5-95% (non-condensing)