

# SP-1001BIE-01-SP1 SynLink Smart PDU

## 1U Single Phase Switched

Remotely switch 8x individual outlets for complete control of your equipment. Each unit comes with a SynLink Smart Control Module that allows you to remotely manage your Power Distribution using industry-standard Network Protocols such as SNMP, Web, HTTP(s), SSH, Telnet, Serial, and more. See the Datasheet for all features supported and make sure to test our live web demo today!

### Smart PDU Features

- Network Protocols: SSH, Telnet, HTTP(S), SNMP, SMTP, and more...
- Inlet Power Monitoring: Current RMS (A)
- Programmable: Custom event triggers and actions, task scheduling, custom alerts, custom event logging.
- Out-of-Band: USB-Serial Port (FTDI chip set), RS232 Serial Port, SynLink Expansion Port.
- Easy Setup: Front Panel LCD interface for rapid deployment.
- Sensors Supported: Temperature & humidity.

### Additional Features

- Inlet Current RMS Measurements
- Individual Outlet Switching
- UL/CSA 62368-1 : 2019 Third Edition Listed

### What's Included

- Detachable NEMA 5-15P to C19 Cord (6ft)
- 1U Mounting Brackets with M4 Screws
- Quick Start Guide Reference Pamphlet

### Key Stats

Form Factor: 1U  
Max Input Current: 20A (16A)  
Power Capacity: 1.9kVA  
Inlet Voltage(s): 120V  
# Outlets: 8

### Applications

- Mission critical remote installations.
- IT server racks.
- Datacenters
- Production automation.
- Test automation.
- Engineering labs.
- R&D facilities.



## Features



### Input Power Measurements

Current Measurements at Input



### Outlet Switching

Each outlet is equipped with a relay to allow for manual or automatic switching. Sequential outlet sequencing built-in to minimize inrush current.



### Relay Health Monitor

Proprietary firmware keeps track of key relay health indicators to alert the user of potential failures. Additional relay failure detection circuit allows for alerts when a failure occurs.



### Surge Protection

Protect devices, prevent downtime, and improve system reliability due to transients and surges.



### Ethernet Port 10/100Mbps

10/100 Base-T Ethernet port. Supports: SSH, Web Server, SNMP, SMTP, NTP, Syslog, HTTP/HTTPS, Telnet, IP4



### Hot-Swappable Control Module

PDU's with this feature can hot swap control modules for upgrade or service while maintaining power to the outlets.



### Local LCD Display

Color 1.8" TFTLCD or 2x8 Character LCD display Displays PDU metrics, Control and configure settings, Alert notifications



### Serial Port

Serial port for access to PDU configuration and data



### Environment Sensor Port

Sensors supported: Temp/Humidity



### SynLink Ports

Daisy chain multiple PDU's to reduce network port footprint in the datacenter.

# Specifications

Input	
Plug Type	IEC-320 C20
Input Voltage	120V
Max Input Current (Derated)	20A (16A)
Phase	1
Input Energy/Power Measurements	Current RMS (A)
Surge Protection	Included

Output	
Outlet Receptacles	NEMA 5-20R(8)
Total Number of Outlets	8
Power Capacity	1.9kVA
Overload Protection	None
Outlet Switching	Included
Outlet Current Measurement	None

Physical	
Form Factor	1U
Dimensions	17.00" x 1.75" x ?
Maximum Operating Elevation	0-10,000 ft / 0 - 3,000 m
Operating Temperature Range	0C to +65C
Relative Humidity	5-95% (non-condensing)

Access & Communications	
Networking Protocols	SNMP V1,2,3, HTTP(S) API, Web Interface, SMTP, Syslog, Telnet, SSH, Ping, DHCP, NTP
Serial Communication (OOB)	RJ45 RS232 Serial and USB-Serial (FTDI)
Ports	1 x USB 2.0 1 x USB-Serial (FTDI) 2 x Sensor Ports 1 x 10/100 BaseT Ethernet 1 x RJ45 RS232 Serial
Front Panel LCD	Allow/Restrict users to manage networking & outlet configuration.
Firmware Upgrade	Updates with an active internet connection, remotely with web GUI, locally with USB Flash Drive