

# SP-4004ANI-09 SynLink Smart PDU

## 0U Single Phase Switched Pro+ ATS

Add power redundancy to your system with Automatic Transfer Switching (ATS). Our ATS PDU continually monitors your primary power source and instantly switches to a secondary source when it detects an outage, without loss of power to your equipment. ATS automatically switches back to primary source when power is restored. Report real-time inlet-level energy monitoring and outlet-level power metering with 1% accuracy. Remotely switch 24x to 36x individual outlets for complete control of your equipment.

### Smart PDU Features

- Network Protocols: SSH, Telnet, HTTP(S), SNMP, SMTP, and more...
- Inlet Energy Monitoring: current (A), voltage (V), line frequency (Hz), active power (W), apparent power (VA), power factor, energy accumulation (kWh).
- Programmable: Custom event triggers and actions, task scheduling, custom alerts, custom event logging.
- Out-of-Band: USB-Serial Port (FTDI chip set), RS232 Serial Port, SynLink Expansion Port.
- Easy Setup: Front Panel LCD interface for rapid deployment.
- Sensors Supported: Temperature & humidity.

### Additional Features

- Inlet Energy Measurements with kWh, amperage, voltage measurements, etc..
- Individual Outlet Switching
- Individual Outlet Current Measurements
- Relay Health Monitoring

### What's Included

- Attached NEMA L6-20P Plug
- 0U Mounting Bracket with M4 Screws
- 0U Toolless Button Kit
- Quick Start Guide Reference Pamphlet

### Key Stats

Form Factor: 0U

Max Input Current: 20A (16A)

Power Capacity: 3.3kVA, 3.8kVA

Inlet Voltage(s): 208V,240V

# Outlets: 16

### Applications

- Mission critical remote installations.
- IT server racks.
- Datacenters
- Production automation.
- Test automation.
- Engineering labs.
- R&D facilities.

## Features



### Inlet Energy Monitor

Energy Metrics: Voltage (V), Current (A), Active Power (W), Line Frequency, Active Power, Active Energy, Reactive Energy, Power Factor



### Automatic Transfer Switch (ATS)

Automatic transfer switch PDUs have dual inlets. The second inlet acts as the backup power source to provide power redundancy to equipment with only one power supply.



### Outlet Current Meter

Current (A) is measured at each outlet



### Outlet Switching

Each outlet is equipped with a relay to allow for manual or automatic switching. Sequential outlet sequencing built-in to minimize inrush current.



### Relay Health Monitor

Proprietary firmware keeps track of key relay health indicators to alert the user of potential failures. Additional relay failure detection circuit allows for alerts when a failure occurs.



### Ethernet Port 10/100Mbps

10/100 Base-T Ethernet port. Supports: SSH, Web Server, SNMP, SMTP, NTP, Syslog, HTTP/HTTPS, Telnet, IP4



### Hot-Swappable Control Module

PDUs with this feature can hot swap control modules for upgrade or service while maintaining power to the outlets.



### Local LCD Display

Color 1.8" TFTLCD or 2x8 Character LCD display Displays PDU metrics, Control and configure settings, Alert notifications



### Serial Port

Serial port for access to PDU configuration and data



### Environment Sensor Port

Sensors supported: Temp/Humidity



### SynLink Ports

Daisy chain multiple PDUs to reduce network port footprint in the datacenter.

# Specifications

Input	
Plug Type	NEMA L6-20P
Input Voltage	208V,240V
Max Input Current (Derated)	20A (16A)
Phase	1
Input Energy/Power Measurements	Kilowatt hours (kWh), Current RMS (A), Line Frequency (Hz), Voltage RMS (V), Active Power (W), Apparent Power (VA), Power Factor

Physical	
Form Factor	OU
Dimensions	65.25" x 2.20" x 2.76"
Maximum Operating Elevation	0-10,000 ft / 0 - 3,000 m
Operating Temperature Range	0C to +65C
Relative Humidity	5-95% (non-condensing)

Output	
Outlet Receptacles	C13(20) + C19(4)
Total Number of Outlets	16
Power Capacity	3.3kVA, 3.8kVA
Overload Protection	None
Outlet Switching	Included
Outlet Current Measurement	Included

Access & Communications	
Networking Protocols	SNMP V1,2,3, HTTP(S) API, Web Interface, SMTP, Syslog, Telnet, SSH, Ping, DHCP, NTP
Serial Communication (OOB)	RJ45 RS232 Serial and USB-Serial (FTDI)
Ports	1 x USB 2.0 1 x USB-Serial (FTDI) 2 x Sensor Ports 1 x 10/100 BaseT Ethernet 1 x RJ45 RS232 Serial
Front Panel LCD	Allow/Restrict users to manage networking & outlet configuration.
Firmware Upgrade	Updates with an active internet connection, remotely with web GUI, locally with USB Flash Drive